


Rockfon[®] Intaline[™] Round Base Baffle System

Products

- Metal baffle to mask plenum for interior spaces.
- 100% random access to plenum.
- Tee grid based system for ease of installation.
- Variable and indexed baffle spacing option available.

Applications

- Airports
- Passenger Terminals
- Corridors
- Assembly Halls



Rockfon[®] Intaline[™] Round Base Baffle System


LEED® v4.1 Highlights


Materials and Resources (MR)

Waste Management Planning Interiors Life Cycle Impact Reduction Environmental Product Declarations Sourcing of Raw Materials Material Ingredients Waste Management Indoor Environmental Quality (EQ)

Low-Emitting Materials Interior Lighting Acoustic Performance

Recycled Content: 78% Aluminur






Standard length is 12'.

Available in lengths from 3' to 16'.

Rockfon® Intaline™ Round Base Baffle System Color Chart



Colors shown are reproduced as close as possible to actual product color within the limitations of printing technology. Color chips are available upon request and should be reviewed before making a final selection. Variations in color matches of system components to ceiling panels can result from slight differences in texture, room lighting, painting process and subjectivity of observers.

As stated in CISCA's "Metal Ceilings Technical Guidelines," site conditions can impact installed visual appearance of metal ceilings. Usage of high gloss and metallic finishes in areas of critical lighting may alter final appearance and should be considered for finish selection.

Suspension Systems

Cubegrid Suspension Components						
	Product Number	Description	Duty Rating	Length	Slotting	Finish
1.	C1800M08	HD Main Runner	Heavy Duty	12'	4' OC	Black
	C1800K08	HD Main Runner	Heavy Duty	12'	2' OC	Black
	C1811M08	ID Main Runner	Intermediate Duty	12'	4' OC	Black
	C1811K08	ID Main Runner	Intermediate Duty	12'	2' OC	Black
1	C1804M	4' Cross Tee	-	4'	None	Black
	C1804K	4' Cross Tee	-	4'	Midpoint	Black

Component Load Test Data			
		Hanger Spacing	
Main Tee	Length	ASTM C-635 4'	5'
C1800	12'	Heavy Duty	8.9
C1811	12'	Intermediate Duty	7.3
Cross Tee	Length	4'	2'
C1804	4'	16	*


^{*}Suspension system for Intaline based on 1800 suspension grid system. Reference ICC-ES Evaluation Report ESR-2631 for testing information.


Perimeter Components and Accessories

Perimeter Wall Angle					
Product	Catalog Number	Description	Unit of Measure	Material	
	C3228.xx	1" x 2" x 12' Wall Angle Painted 360 Degrees	PC	Steel	
	38.90.124.xxx	15/16" x 3/4" x 12' Wall Angle Finished Outside Only 300 Feet Per Carton	CTN	Aluminum	

Accessory Items					
Product	Catalog Number	Description	Unit of Measure	CTN Qty	
	38.40.921.008	Baffle Suspension Clip for 15/16" Grid - Black	CTN	100 pcs	
	38.40.923	Baffle Bottom Alignment Clip - Clear	CTN	50 pcs	
	38.20.922	Baffle Top Alignment Clip - Clear	CTN	100 pcs	

Installation







Properties

Material

0.032" Aluminum



Fire Performance

Surface burning characteristics: UL723 (ASTM E84) Flame Spread Index: 0 Smoke Developed Index: 0



Environment

Aluminum: 78% recycled content Steel: 30% recycled content 100% locally recyclable



Warranty

1-Year Limited Product Warranty See rockfon.com



Hygiene

Metal provides no sustenance to microorganisms



Cleaning

✓ Damp cloth

070924

Rockfon

4849 S. Austin Ave. Chicago, IL 60638 USA

Tel. +1-800-323-7164 cs@rockfon.com rockfon.com

2024 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL A/S 2022. All rights reserved.

[®] denotes a trademark that is registered in the United States of America.