

Rockfon® Color-all™



Features & Benefits

- 34 exclusive colors for acoustic ceiling and wall solutions to inspire and enhance the interior design scheme
- Smooth surface
- Excellent sound absorption (NRC = 0.85 - 0.95)
- Fire Performance - Class A
- Optimal design freedom due to the variety of edges (lay-in, tegular and concealed) and colors

Applications

- Office
- Industry
- Healthcare
- Retail
- Classroom
- Restaurant
- Reception
- Auditorium



High Acoustic Absorption



Class A Fire Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics



Mold and Mildew Resistance



30-year Warranty Applies to All Stone Tiles and Panels

Rockfon® Color-all™

LEED® v4.1 Highlights

Materials and Resources (MR)

- Interiors Life Cycle Impact Reduction ✓
- Environmental Product Declarations ✓
- Sourcing of Raw Materials ✓
- Material Ingredients -
- Waste Management -

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- Interior Lighting ✓
- Acoustic Performance ✓

Recycled Content 41%***

High Performance Factors

Base Material	Stone Wool
Surface	Smooth White Surface
Fire	Class A
Performance	Tested to US Standard ASTM E84: Flame Spread Index: 5-15 Smoke Developed Index: 0 Canadian Standard CAN/ULC S102: Flame Spread Index: 15 Smoke Developed Index: 5
Warranty	30-Year Tile Warranty

Mold & Mildew Resistance	Inherently Resistant (applies to stone wool substrate and tile surfaces) Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Tiles Pass)
-------------------------------------	---

Sag Resistance	Won't Sag or Warp Even in 100% Relative Humidity Tested to ASTM C367
-----------------------	---

Low VOC	UL GREENGUARD Gold Certified
----------------	------------------------------



Standard Panels



Packaging Information

Edge Designation	Item Number	Modular Size* (nominal)	NRC	Fire Class	Mold & Mildew Resistance	Sag Resistance (relative humidity)	Light Reflectance	Embodied Carbon		Low VOC	lbs/sqft	sqft/carton
								Per 1m ² (kg CO ₂ - eq)	Per 1ft ² (kg CO ₂ - eq)			
 SQ Square Lay-In	11100	2' x 2' x 5/8"	0.90	A	✓	up to 100%	Color Dependant	3.36	0.312	✓	0.47	112
	11101	2' x 4' x 5/8"	0.90	A	✓	up to 100%	Color Dependant	3.36	0.312	✓	0.47	112
 SL Square Tegular	11250	2' x 2' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	0.69	40
	11251	2' x 4' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	0.69	80
 SLN Square Tegular Narrow	11200	2' x 2' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	0.69	40
	11201	2' x 4' x 3/4"	0.95	A	✓	up to 100%	Color Dependant	3.49	0.325	✓	0.69	80
 CDX Fully Concealed	11600	2' x 2' x 7/8"	0.95	A	✓	up to 100%	Color Dependant	3.75	0.350	✓	0.75	40
	11601	2' x 4' x 7/8"	0.95	A	✓	up to 100%	Color Dependant	3.75	0.350	✓	0.75	80

* Refer to the Rockfon® Module System brochure for module tile sizes.

***Recycled content values for our stone wool tiles and panels are based on 2020 production averages of a standard 2' x 2' tile and based on their primary production location.

Minimum Order Quantities** for Rockfon® Color-All™

All Rockfon Color-All Square Edge (SQ) 2' x 2' and 2' x 4' tiles = 300 sqft minimum. Minimums do not apply to Color-all Standard Program.** For any other sizes, please contact Rockfon Customer Service.

SL, SL, SLN, and CDX edges in all dimensions in all 34 Color-all colors = 6,000 sqft. Minimums do not apply to Color-all Standard Program.** (Different edges and dimensions can be mixed in the same color. The quantity per dimension/edge must be 1,000 sqft and the total quantity must be 6,000 sqft.)

**Minimum order quantities do not apply to matching Color-All grid products and 4 Color-all Standard Program Colors: 701 Stone, 706 Concrete, 723 Hemp, 709 Charcoal. For further questions please contact Rockfon Customer Service.

Product Compatibility


15/16" Suspension Systems	9/16" Suspension Systems
200, 1200 and Fire Rated systems	4000, 4200, 4500 and Fire Rated systems
 SQ Square Lay-in	 SLN - Square Tegular Narrow
 SL Square Tegular	 4000 - Tempra
 CDX Fully Concealed	 4200 - Integrity
	 4500 - Ultraline 1/4" reveal

Rockfon® Color-all™ Standard Program Colors



Charcoal

Light reflectance: 0.04



Concrete

Light reflectance: 0.16



Hemp

Light reflectance: 0.45




Stone

Light reflectance: 0.55


Please refer to Rockfon® Color-all™ Standard Program Datasheet for more details.

Additional Rockfon® Color-all™ Colors




Mustard

Light reflectance: 0.36




Sand

Light reflectance: 0.55




Stucco

Light reflectance: 0.70




Scarlet

Light reflectance: 0.08




Coral

Light reflectance: 0.21




Seashell

Light reflectance: 0.55




Petal

Light reflectance: 0.70




Seaweed

Light reflectance: 0.05




Eucalyptus

Light reflectance: 0.12




Sage

Light reflectance: 0.34




Mint

Light reflectance: 0.70




Space

Light reflectance: 0.04



Storm

Light reflectance: 0.08



Azure

Light reflectance: 0.34



Fresh


Light reflectance: 0.51

The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool. Samples of the colored surfaces are available upon request.


Additional Rockfon® Color-all™ Colors



Light reflectance: 0.22



Light reflectance: 0.22




Light reflectance: 0.29



Light reflectance: 0.49



Light reflectance: 0.51




Light reflectance: 0.04




Light reflectance: 0.30




Light reflectance: 0.07



Light reflectance: 0.33




Light reflectance: 0.33



Light reflectance: 0.44




Light reflectance: 0.07



Light reflectance: 0.34



Light reflectance: 0.58



Light reflectance: 0.74

The actual color of the ceiling tiles may deviate slightly from printed colors due to the texture of the surface and the underlying color of stone wool. Samples of the colored surfaces are available upon request.

Rockfon® Color-all™

Accessories

	Detail	Rockfon Part Number	Product Number	Product Description	Packaging	
					Pcs/ Ctn	Lbs/ Ctn
General Clips*		250348	935.00	Universal Hold Down Clip	1000	16
		252923	425.01	Hold Down Clip for 5/8" Board 250/1250 Systems	200	2
		250343	820.00	Hold Down Clip for 5/8" Board 250/1250 Systems	1000	7
		237949	490.00	Hold Down Clip for 0" - 3/4" Panels (Black)	100	2
		237952	491.00	Hold Down Clip for 3/4" - 1-1/4" Panels (Blue)	150	2
		237954	492.00	Hold Down Clip for 1-1/2" Panels (Grey)	100	2
		250324	426.01	Butterfly Retention Clip for 0" - 1" Panels	200	15
250325		427.01	Butterfly Retention Clip for 1" - 2" Panels	150	15	

*Clips should be chosen as per tile thickness

**Scan for Full
Accessories Guide**



Rockfon® Color-all™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied water-based paint on glass scrim surface.



ASTM E1264 Classification

ASTM E1264 (2022) : Type IV, Form 3, Pattern G
ASTM E1264 (2023): Type A, Form A2.3, Pattern G



Fire Performance

Stone wool ceiling tiles achieve Class A fire requirements and are tested for Surface Burning Characteristics to ASTM E84 for the US and CAN/ULC S102 for Canada.

Rockfon® Color-all™ Surface burning characteristics:
UL723 (ASTM E84): Flame Spread Index: 5-15
Smoke Developed Index: 0
CAN/ULC S102: Flame Spread Index: 15
Smoke Developed Index: 5



Mold and Mildew Resistance

Rockfon® Color-all™ stone wool substrate and tile surfaces are inherently resistant to mold and mildew and are tested to ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings) and ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings).



Humidity Resistance

Stone wool ceiling tiles are inherently resistant and are tested to ASTM C367 (Standard Test Methods for Strength Properties of Prefabricated Architectural Acoustical Tile or Lay-In Ceiling Panels) and won't sag or warp even in 100% relative humidity.



Cleaning

✓ Vacuum



Sustainability

Rockfon® Color-all™ Stone wool ceiling tiles are UL GREENGUARD Gold certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ GREENGUARD Gold available*
 - ✓ Environmental Product Declaration available*
- *Applicable to all edge types



Environment

41% recycled content. Recycled content based on European manufacturing.



Embodied Carbon

Global Warming Potential (GWP) kg of CO₂-eq (per functional unit) from stages A1 - A3 for SQ Edge: 3.36 kg CO₂-eq (per 1m²)* / 0.312 kg CO₂-eq (per 1f²)*
*For all other edge types, refer to p. 2



Thermal Resistance

R 3.47 hr.ft².°F/Btu per 1 inch (I-P)
R 0.61 m².K/W per 25.4 mm (SI)



Tile Directionality

Rockfon Color-all® tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180° not 90°.



Warranty

30-Year Limited Product Warranty
See rockfon.com



GREENGUARD Gold Certified for Office and Educational Environments



CERTIFIED Environmental Product Declaration

Find us on

MasterSpec®

Powered by Deltek Specpoint®

BIM/Revit objects available at:
rockfon.com/products/rockfon-color-all/

081524

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2024 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL A/S 2022. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164

cs@rockfon.com

rockfon.com