

Rockfon® Facett™




Features & Benefits

- Designed for enclosed parking garages and light industrial applications
- Delivers excellent sound absorption with an NRC of 1.00
- Provides thermal insulation, achieving up to R 13.85 hr.ft².°F/Btu for 4 inch (I-P), enhancing energy efficiency and indoor comfort
- Class A fire performance ensures safety with 0 Smoke Development and 5 Flame Spread per ASTM E84
- Compliant with the Build America, Buy America Act (BABAA)

Applications

- Enclosed Garage
- Light Industry
- Heavy Industry



High Acoustic Absorption



Class A Fire Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics



Mold and Mildew Resistance



30-year Warranty Applies to All Stone Tiles and Panels

Rockfon® Facett™

LEED® v4.1 Highlights

Materials and Resources (MR)

- Waste Management Planning -
- Interiors Life Cycle Impact Reduction ✓
- Environmental Product Declarations ✓
- Sourcing of Raw Materials ✓
- Material Ingredients ✓
- Waste Management -

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- Interior Lighting ✓
- Acoustic Performance ✓

Recycled Content: 52%*

High Performance Factors

Base Material	Stone Wool
Surface	Lightly Textured White
Fire	Class A
Performance	Tested to US Standard ASTM E84: Flame Spread Index: 0 Smoke Developed Index: 5 Canadian Standard CAN/ULC S102: Flame Spread Index: 5 Smoke Developed Index: 0
Warranty	30-Year Tile Warranty

Mold & Mildew Resistance	Inherently Resistant (applies to stone wool substrate and tile surfaces) Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Tiles Pass)
Sag Resistance	Won't Sag or Warp Even in 100% Relative Humidity Tested to ASTM C367
Low VOC	UL GREENGUARD Gold Certified



Standard Panels



Packaging Information

Edge Designation	Item Number	Modular Size (nominal)	NRC	Fire Class	Mold & Mildew Resistance	Sag Resistance (relative humidity)	Light Reflectance	Embodied Carbon		Low VOC	lbs/sqft	sqft/carton
								Per 1m ² (kg CO ₂ - eq)	Per 1ft ² (kg CO ₂ - eq)			
 SQ Square Lay-in	5100	2' x 4' x 1 1/2"	1.00	A	✓	up to 100%	0.68	4.02	0.373	✓	0.82	40
	5200	2' x 4' x 4"	1.00	A	✓	up to 100%	0.68	8.77	0.815	✓	1.93	16





*Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2' x 2' tile and their primary production location.

Product Compatibility

15/16" Suspension Systems
200, 1200 and Fire Rated systems
 SQ Square Lay-in



Rockfon® Facett™

Accessories

	Detail	Rockfon Part Number	Product Number	Product Description	Packaging	
					Pcs/ Ctn	Lbs/ Ctn
General Clips*		260623	495.00**	Hold Down Clip Kit for 2" - 4"	100	2
		250348	935.00	Universal Hold Down Clip	1000	16
		237954	492.00	Hold Down Clip for 1-1/2" Panels (Grey)	100	2
		250324	426.01	Butterfly Retention Clip for 0" - 1" Panels	200	15

*Clips should be chosen as per tile thickness

**The 495.00 Hold Down is specifically designed for Facett 2" - 4" thick panels. This is a 2-piece system, with one vertical piece which is installed and secured to the grid, and the secondary wire piece, which is inserted into the clip at the proper height to accommodate the ceiling tile.



Scan for Full Accessories Guide



Rockfon® Facett™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied water-based paint on glass scrim surface.



ASTM E1264 Classification

ASTM E1264 (2022): Type IV, Form 3, Pattern E
ASTM E1264 (2023): Type A, Form A2.3, Pattern E



Fire Performance

Stone wool ceiling tiles achieve Class A fire requirements and are tested for Surface Burning Characteristics to ASTM E84 for the US and CAN/ULC S102 for Canada.

Rockfon® Facett™ Surface burning characteristics:
UL723 (ASTM E84): Flame Spread Index: 0
Smoke Developed Index: 5
CAN/ULC S102: Flame Spread Index: 5
Smoke Developed Index: 0



Mold and Mildew Resistance

Rockfon® Facett™ stone wool substrate and tile surfaces are inherently resistant to mold and mildew and are tested to ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings) and ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings).



Humidity Resistance

Stone wool ceiling tiles are inherently resistant and are tested to ASTM C367 (Standard Test Methods for Strength Properties of Prefabricated Architectural Acoustical Tile or Lay-In Ceiling Panels) and won't sag or warp even in 100% relative humidity.



Cleaning

- ✓ Vacuum
- ✓ Damp cloth



Sustainability

Rockfon® Facett™ stone wool acoustic solutions are UL GREENGUARD Gold certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments.

Selected potential applications: LEED, WELL, CHPS, LBC, Green Globes, BREEAM Int. and CALGreen

- ✓ UL GREENGUARD Gold
- ✓ Environmental Product Declaration (Product-Specific, Type III)



Environment

52% recycled content. Recycling content based on the primary production location.



Embodied Carbon

Global Warming Potential (GWP) kg of CO₂-eq (per functional unit) from stages A1 - A3 for SQ Edge: 4.02 kg CO₂-eq (per 1m²*) / 0.373 kg CO₂-eq (per 1f²*)
*For all other thicknesses, refer to p. 2



Thermal Resistance

R 5.20 hr.ft².°F/Btu for 1-1/2 inch (I-P)
R 0.92 m².K/W per 38.1 mm (SI)
R 13.85 hr.ft².°F/Btu for 4 inch (I-P)
R 2.44 m².K/W per 101.6 mm (SI)



Tile Directionality

Rockfon® Facett™ tiles are directional and must be installed according to backside arrow direction. The arrow can be turned 180°, not 90°.



Warranty

30-Year Limited Product Warranty
See rockfon.com



GREENGUARD Gold Certified
for Office and Educational
Environments



CERTIFIED Environmental
Product Declaration

Find us on

MasterSpec®

Powered by Deltek Specpoint®

BIM/Revit objects available at:
rockfon.com/products/rockfon-facett/

090324

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2024 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL A/S 2022. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164

cs@rockfon.com

rockfon.com