

# Rockfon® Medical™ Standard





## Features & Benefits

- Designed to meet essential cleaning and hygiene requirements for general healthcare areas
- Excellent sound absorption with NRC 0.90 that helps create a healing environment
- Meets FGI guidelines for healthcare facilities
- Has a low particle emission achieving ISO Class 5 per ISO14644-1 using Chicago Metallic® BarrierGrid® for better air cleanliness
- Tested per ASTM D4828 for washability and ASTM D2486 for scrub resistance
- Inherently mold and mildew resistant without added antimicrobials
- UL GREENGUARD Gold certified for low chemical emissions
- Compliant with the Build America, Buy America Act (BABAA)

## Applications

- Nurses' Station
- Waiting Area
- Reception
- Office
- Corridor



**High Acoustic Absorption**



**Class A Fire Performance**



**Moisture and Sag Resistance**



**Smooth, Modern Aesthetics**



**Mold and Mildew Resistance**



**30-year Warranty Applies to All Stone Tiles and Panels**

# Rockfon® Medical™ Standard

## LEED® v4.1 Highlights

### Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

### Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- Interior Lighting ✓
- Acoustic Performance ✓

**Recycled Content:** 43%\*




## High Performance Factors

<b>Base Material</b>	Stone Wool
<b>Surface</b>	Lightly Textured
<b>Fire Performance</b>	Class A Tested to US Standard ASTM E84: Flame Spread Index: 0 Smoke Developed Index: 0 Canadian Standard CAN/ULC S102: Flame Spread Index: 15 Smoke Developed Index: 5
<b>Warranty</b>	30-Year Tile Warranty

<b>Mold &amp; Mildew Resistance</b>	Inherently Resistant (applies to stone wool substrate and tile surfaces) Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Tiles Pass)
<b>Sag Resistance</b>	Won't Sag or Warp Even in 100% Relative Humidity Tested to ASTM C367
<b>Low VOC</b>	UL GREENGUARD Gold Certified










## Standard Panels

Edge Designation	Item Number	Modular Size (nominal)	NRC	AC	Fire Class	Mold & Mildew Resistance	Light Reflectance	Cleanroom Class	Embodied Carbon		Sag Resistance (relative humidity)	Low VOC	Packaging Information	
									Per 1m <sup>2</sup> (kg CO <sub>2</sub> - eq)	Per 1ft <sup>2</sup> (kg CO <sub>2</sub> - eq)			lbs/sqft	sqft/carton
 SQ Square Lay-In	33200	2' x 2' x 5/8"	0.90	170	A	✓	0.86	ISO 5	2.04	0.190	up to 100%	✓	0.38	112
	33201	2' x 4' x 5/8"	0.90	170	A	✓	0.86	ISO 5	2.04	0.190	up to 100%	✓	0.38	112
 SLN Square Tegular Narrow	33225	2' x 2' x 5/8"	0.90	170	A	✓	0.86	ISO 5	2.43	0.226	up to 100%	✓	0.47	56
	33226	2' x 4' x 5/8"	0.90	170	A	✓	0.86	ISO 5	2.43	0.226	up to 100%	✓	0.47	112
 SL Square Tegular	33250	2' x 2' x 5/8"	0.90	170	A	✓	0.86	ISO 5	2.43	0.226	up to 100%	✓	0.47	56
	33251	2' x 4' x 5/8"	0.90	170	A	✓	0.86	ISO 5	2.43	0.226	up to 100%	✓	0.47	112

\*Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2'x2' tile, and based on their primary production location.

## Product Compatibility

15/16" Suspension Systems		9/16" Suspension Systems	
200, 1200 and Fire Rated Systems	Chicago Metallic® BarrierGrid®*	4000, 4500, 4600 and Fire Rated Systems	
 SQ Square Lay-in	 SL Square Tegular	 SQ Square Lay-in	   
			4000 - Tempra    4000 - Tempra    4500 - Ultraline 1/4" Reveal    4600 - Ultraline 1/8" Reveal

\*Rockfon® Medical™ Standard achieves ISO Class 5 using Chicago Metallic® BarrierGrid®

# Rockfon® Medical™ Standard

## Accessories

	Detail	Rockfon Part Number	Product Number	Product Description	Packaging	
					Pcs/ Ctn	Lbs/ Ctn
General Clips*		250348	935.00	Universal Hold Down Clip	1000	16
		252923	425.01	Hold Down Clip for 5/8" Board 250/1250 Systems	200	2
		250343	820.00	Hold Down Clip for 5/8" Board 250/1250 Systems	1000	7
		237949	490.00	Hold Down Clip for 0" - 3/4" Panels (Black)	100	2
		237952	491.00	Hold Down Clip for 3/4" - 1-1/4" Panels (Blue)	150	2
		237954	492.00	Hold Down Clip for 1-1/2" Panels (Grey)	100	2
		250324	426.01	Butterfly Retention Clip for 0" - 1" Panels	200	15
		250325	427.01	Butterfly Retention Clip for 1" - 2" Panels	150	15
Tile Paint		307988	RFN941	Edge Paint for Field Cut Panels White - 8 oz	Bottle	1
		307989	RFN941Q	Edge Paint for Field Cut Panels White - 32 oz	Can	1

\*Clips should be chosen as per tile thickness

**Scan for Full  
Accessories Guide**



# Rockfon® Medical™ Standard Properties

## Material

Stone wool (Mineral Wool) ceiling tiles with factory applied water-based paint on glass scrim surface.



### ASTM E1264 Classification

ASTM E1264 (2022): Type IV, Form 3, Pattern E  
ASTM E1264 (2023): Type A, Form A2.3, Pattern E



### Fire Performance

Stone wool ceiling tiles achieve Class A fire requirements and are tested for Surface Burning Characteristics to ASTM E84 for the US and CAN/ULC S102 for Canada.

Rockfon® Medical™ Standard Surface burning characteristics:

UL723 (ASTM E84): Flame Spread Index: 0  
Smoke Developed Index: 0  
CAN/ULC S102: Flame Spread Index: 15  
Smoke Developed Index: 5



### Mold and Mildew Resistance

Rockfon® Medical Standard™ stone wool substrate and tile surfaces are inherently resistant to mold and mildew and are tested to ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings) and ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings).



### Humidity Resistance

Stone wool ceiling tiles are inherently resistant and are tested to ASTM C367 (Standard Test Methods for Strength Properties of Prefabricated Architectural Acoustical Tile or Lay-In Ceiling Panels) and won't sag or warp even in 100% relative humidity.



### Clean Room

ISO Class 5 when used with Chicago Metallic® BarrierGrid®



### Cleaning

- ✓ Vacuum
- ✓ Damp cloth
- ✓ Rockfon® Medical Standard™ tiles are able to be washed through 100 cycles of the standard washability tester and cleaner prescribed in ASTM D4828.
- ✓ Rockfon® Medical Standard™ tiles can withstand up to 100 scrub cycles using the prescribed scrubber and force per ASTM D2486.



### Sustainability

Rockfon® Medical™ Standard tiles are UL GREENGUARD Gold certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ UL GREENGUARD Gold available\*
- ✓ Environmental Product Declaration available\*
- ✓ Health Product Declaration (Product-Specific, Type III)\*

\* Applicable to all edge types



### Environment

43% recycled content. Recycled content based on U.S. manufacturing.



### Embodied Carbon

Global Warming Potential (GWP) kg of CO<sub>2</sub>-eq (per functional unit) from stages A1 - A3 for SQ Edge: 2.04 kg CO<sub>2</sub>-eq (per 1m<sup>2</sup>)\* / 0.190 kg CO<sub>2</sub>-eq (per 1f<sup>2</sup>)\*  
\*For all other edge types, refer to p. 2



### Thermal Resistance

R 2.17 hr.ft<sup>2</sup>.°F/Btu for 5/8 inch (I-P)  
R 0.38 m<sup>2</sup>.K/W for 15.9 mm (SI)



### Warranty

30-Year Limited Product Warranty  
See rockfon.com



GREENGUARD Gold Certified for Office and Educational Environments



CERTIFIED Environmental Product Declaration

Find us on

**MasterSpec**®

Powered by Deltek Specpoint®

BIM/Revit objects available at:  
[rockfon.com/products/rockfon-medical-standard/](http://rockfon.com/products/rockfon-medical-standard/)

081924

**Rockfon**

4849 S. Austin Ave.  
Chicago, IL 60638 USA

2024 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.

© ROCKWOOL A/S 2022. All rights reserved.

® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164

Fax. +1-800-222-3744

[rockfon.com](http://rockfon.com)