

Rockfon Sonar[®] Activity[™]



Features & Benefits

- Achieves superior sound absorption with an NRC of 0.90
- Class A fire performance ensures safety with 0 Smoke Development and 0 Flame Spread per ASTM E84
- Flexibility in design with both suspended and direct mount options
- Supports sustainability goals by contributing to LEED v4.1 criteria

Applications

- Office
- Classroom
- Restaurant
- Reception



High Acoustic Absorption



Class A Fire Performance



Moisture and Sag Resistance



Smooth, Modern Aesthetics



Mold and Mildew Resistance



30-year Warranty Applies to All Stone Tiles and Panels

Rockfon Sonar® Activity™

LEED® v4.1 Highlights

Materials and Resources (MR)

- Waste Management Planning ✓
- Interiors Life Cycle Impact Reduction ✓
- Environmental Product Declarations ✓
- Sourcing of Raw Materials ✓
- Material Ingredients ✓
- Waste Management -

Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- Interior Lighting ✓
- Acoustic Performance ✓

Recycled Content: up to 41%*

High Performance Factors

Base Material	Stone Wool
Surface	Lightly Textured
Fire Performance	Class A Tested to US Standard ASTM E84: Flame Spread Index: 0 Smoke Developed Index: 0 Canadian Standard CAN/ULC S102: Flame Spread Index: 10 Smoke Developed Index: 5
Warranty	30-Year Tile Warranty

Mold & Mildew Resistance	Inherently Resistant (applies to stone wool substrate and tile surfaces) Tested to ASTM D3273: 10 (Scale of 0 to 10, 10 being highest performing) Tested to ASTM C1338: Pass (Pass or Fail, Stone Wool Tiles Pass)
Sag Resistance	Won't Sag or Warp Even in 100% Relative Humidity Tested to ASTM C367
Low VOC	UL GREENGUARD Gold Certified



Standard Panels



Packaging Information

Edge Designation	Item Number	Modular Size (nominal)	NRC	Fire Class	Mold & Mildew Resistance	Sag Resistance (relative humidity)	Light Reflectance	Cleanroom Class	Embodied Carbon		Low VOC	Packaging Information	
									Per 1m ² (kg CO ₂ - eq)	Per 1ft ² (kg CO ₂ - eq)		lbs/sqft	sqft/carton
SQ Square Lay-In	15100	2' x 2' x 1 1/2"	0.90	180	A	up to 100%	0.85	ISO Class 5	6.13	0.570	✓	1.3	40
SLT Angled Tegular	15300	2' x 2' x 1 1/2"	0.90	180	A	up to 100%	0.85	ISO Class 5	6.13	0.570	✓	1.3	20
DMT Direct Mount	15350	2' x 2' x 1 1/2"	0.90	180	A	up to 100%	0.85	ISO Class 5	6.13	0.570	✓	1.3	20

*Recycled content values for our stone wool tiles and panels are based on 2021 production averages of a standard 2'x4' tile, and based on their primary production location.

Product Compatibility

15/16" Suspension Systems	
200, 1200 and Fire Rated Systems	
 SQ Square Lay-in	 SLT Angled Tegular

Rockfon Sonar® Activity™

Accessories

	Detail	Rockfon Part Number	Product Number	Product Description	Packaging	
					Pcs/ Ctn	Lbs/ Ctn
General Clips*		250348	935.00	Universal Hold Down Clip	1000	16
		252923	425.01	Hold Down Clip for 5/8" Board 250/1250 Systems	200	2
		250343	820.00	Hold Down Clip for 5/8" Board 250/1250 Systems	1000	7
		237949	490.00	Hold Down Clip for 0" - 3/4" Panels (Black)	100	2
		237952	491.00	Hold Down Clip for 3/4" - 1-1/4" Panels (Blue)	150	2
		237954	492.00	Hold Down Clip for 1-1/2" Panels (Grey)	100	2
		250324	426.01	Butterfly Retention Clip for 0" - 1" Panels	200	15
		250325	427.01	Butterfly Retention Clip for 1" - 2" Panels	150	15
Tile Paint		307988	RFN941	Edge Paint for Field Cut Panels White - 8 oz	Bottle	1
		307989	RFN941Q	Edge Paint for Field Cut Panels White - 32 oz	Can	1

*Clips should be chosen as per tile thickness

**Scan for Full
Accessories Guide**



Rockfon Sonar® Activity™ Properties

Material

Stone wool (Mineral Wool) ceiling tiles with factory applied water-based paint and water-based laquer on glass scrim surface.



ASTM E1264 Classification

ASTM E1264 (2022): Type IV, Form 3, Pattern E
ASTM E1264 (2023): Type A, Form A2.3, Pattern E



Fire Performance

Stone wool ceiling tiles achieve Class A fire requirements and are tested for Surface Burning Characteristics to ASTM E84 for the US and CAN/ULC S102 for Canada.

Rockfon Sonar® Activity™ Surface burning characteristics:
UL723 (ASTM E84): Flame Spread Index: 0
Smoke Developed Index: 0
CAN/ULC S102: Flame Spread Index: 10
Smoke Developed Index: 5



Mold and Mildew Resistance

Rockfon Sonar® Activity™ stone wool substrate and tile surfaces are inherently resistant to mold and mildew and are tested to ASTM D3273 (Standard Test Method for Resistance to Growth of Mold on the Surface of Interior Coatings) and ASTM C1338 (Standard Test Method for Determining Fungi Growth Resistance of Insulation Materials and Facings).



Humidity Resistance

Stone wool ceiling tiles are inherently resistant and are tested to ASTM C367 (Standard Test Methods for Strength Properties of Prefabricated Architectural Acoustical Tile or Lay-In Ceiling Panels) and won't sag or warp even in 100% relative humidity.



Clean Room

ISO Class 5 using Chicago Metallic® BarrierGrid®



Cleaning

- ✓ Vacuum
- ✓ Damp cloth
- ✓ Rockfon Sonar® Activity can be safely treated with a number of cleaning solutions and are resistant to diluted solutions of ammonia, chlorine, quaternary ammonium and hydrogen peroxide as described in ASTM D1308.



Sustainability

Rockfon Sonar® Activity™ tiles are UL GREENGUARD Gold certified for low VOC (chemical) emissions and meet the California Department of Public Health (CDPH) Standard Method v1.2-2017 for offices and classroom environments.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen

- ✓ UL GREENGUARD Gold*
 - ✓ Environmental Product Declaration (Product-Specific, Type III)*
- * Applicable to all edge types



Environment

Up to 41% recycled content. Recycled content based on U.S. manufacturing.



Embodied Carbon

Global Warming Potential (GWP) kg of CO₂-eq (per functional unit) from stages A1 - A3 for SQ Edge: 6.13 kg CO₂-eq (per 1m²)* / 0.570 kg CO₂-eq (per 1f²)*
*For all other edge types, refer to p. 2



Thermal Resistance

R 5.20.°F/Btu for 1-1/2 inch (I-P)
R 0.92 m².K/W for 38.1 mm (SI)



Warranty

30-Year Limited Product Warranty
See rockfon.com



GREENGUARD Gold Certified for Office and Educational Environments



CERTIFIED Environmental Product Declaration

Find us on

MasterSpec®

Powered by Deltek Specpoint®

BIM/Revit objects available at:
rockfon.com/products/rockfon-sonar-activity/

801324

Rockfon

4849 S. Austin Ave.
Chicago, IL 60638 USA

2024 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.
© ROCKWOOL A/S 2022. All rights reserved.
® denotes a trademark that is registered in the United States of America.

Tel. +1-800-323-7164
Fax. +1-800-222-3744
rockfon.com